



Benford

A Terex Company



6 in 1 control lever.

Operator isolated from vibration.

Fuel, water, hydraulic tanks removable.

Freewheel facility.

Plastic water tank enclosed in steel.

Anti vandal protection.

Unique steering arm.

Low noise levels.

Excellent serviceability.

TV1000 TV1200 Tandem Rollers

TV1000 TV1200 Machine Data

	TV1000	TV1200
Weight		
Basic Weight kg	2376	2711
Operating Weight kg	2560	2895
Static Linear Load kg/ m	1280	1206
Vibration		
Frequency Hz	51.0	51.0
Amplitude mm	0.5	0.6
Centrifugal Force kN	21.0	29.0
Engine		
Model	Deutz F2L1011F	
Cylinders	2.0	
Cooling	Air	
Power (kW)	19.5	
RPM	2500	
Drive		
KPH	10	
Gradeability % vib on	30	
Gradeability % vib off	40	
Dimensions		
Drum Width mm	1000	1200
Drum Diameter mm	700	700
Drum Thickness mm	10	13
Machine Width mm	1070	1270
Machine Length mm	2375	2375
Machine Height With ROPS mm	2650	2650
Machine Height Without ROPS mm	1850	1850
Ground Clearance mm	210	210
Wheelbase mm	1675	1675
Inside turning Radius mm	3075	2975
Frame Articulation degrees	30	30
Frame Oscillation degrees	15	15
Hydraulic Tank Capacity litres	35	35
Fuel Tank Capacity litres	38	38
Water Tank Capacity litres	180	180
Benford reserve the right to alter these specifications		

Benford Ltd. The Cape, Warwick, England. CV34 5DR
 Tele. +44(0)1926 493466 Fax +44(0)1926 490985
 E-Mail sales@benford.co.uk www.benfords.com