



Benford

A Terex Company



6 in 1 control lever.

Operator isolated from vibration.

Fuel, water, hydraulic tanks removable.

Freewheel facility.

Plastic water tank enclosed in steel.

Anti vandal protection.

Unique steering arm.

Low noise levels.

Excellent serviceability.

TV1000 TV1200 Tandem Rollers

TV1000 TV1200 Machine Data

| | TV1000 | TV1200 |
|---|----------------|--------|
| Weight | | |
| Basic Weight kg | 2376 | 2711 |
| Operating Weight kg | 2560 | 2895 |
| Static Linear Load kg/ m | 1280 | 1206 |
| Vibration | | |
| Frequency Hz | 51.0 | 51.0 |
| Amplitude mm | 0.5 | 0.6 |
| Centrifugal Force kN | 21.0 | 29.0 |
| Engine | | |
| Model | Deutz F2L1011F | |
| Cylinders | 2.0 | |
| Cooling | Air | |
| Power (kW) | 19.5 | |
| RPM | 2500 | |
| Drive | | |
| KPH | 10 | |
| Gradeability % vib on | 30 | |
| Gradeability % vib off | 40 | |
| Dimensions | | |
| Drum Width mm | 1000 | 1200 |
| Drum Diameter mm | 700 | 700 |
| Drum Thickness mm | 10 | 13 |
| Machine Width mm | 1070 | 1270 |
| Machine Length mm | 2375 | 2375 |
| Machine Height With ROPS mm | 2650 | 2650 |
| Machine Height Without ROPS mm | 1850 | 1850 |
| Ground Clearance mm | 210 | 210 |
| Wheelbase mm | 1675 | 1675 |
| Inside turning Radius mm | 3075 | 2975 |
| Frame Articulation degrees | 30 | 30 |
| Frame Oscillation degrees | 15 | 15 |
| Hydraulic Tank Capacity litres | 35 | 35 |
| Fuel Tank Capacity litres | 38 | 38 |
| Water Tank Capacity litres | 180 | 180 |
| Benford reserve the right to alter these specifications | | |

Benford Ltd. The Cape, Warwick, England. CV34 5DR
 Tele. +44(0)1926 493466 Fax +44(0)1926 490985
 E-Mail sales@benford.co.uk www.benfords.com