

产品参数 Product Parameter

作业参数 Operation Parameter			
A	最大操作高度 Maximum operation height	mm	3850
B	至铲斗销的高度 Height between bucket pin and ground	mm	3002
C	至司机室顶的高度 Height between cab top and ground	mm	2014
D	铲斗水平时至其底部的最大高度 Maximum height between horizontal bucket bottom and ground	mm	2834
E	不带附件时的长度 Length not including accessories	mm	2604
F	带标准铲斗的长度 Length including standard bucket	mm	3318
G	最大高度时的卸载角 Unloading angle at the largest height	°	42
H	卸载高度 Unloading height	mm	2320
J	卸载距离 Unloading distance	mm	475
K	铲斗在地面的翻转角 Flip angle of bucket on the ground	°	30
L	铲斗在最高时的翻转角 Flip angle of bucket at the largest height	°	97
M	轴距 Wheelbase	mm	987
P	离地间隙 Ground clearance	mm	220
Q	离去角 Departure angle	°	25
R	不带附件时的前转弯半径 Front turning radius not including accessories	mm	1235
S	前转弯半径 Front turning radius	mm	1953
T	后转弯半径 Rear turning radius	mm	1531
U	尾部长度 Tail length	mm	1021
V	轮距 Wheel span	mm	1293
W	铲斗宽度 Bucket width	mm	1600
性能 Performance			
	整机重量 Overall weight	kg	2830
	装载量 Loading capacity	kg	750
	倾覆载荷 Tipping load	kg	1500
	铲斗掘起力 Digging force of bucket	kg	2000
	动臂掘起力 Digging force of boom	mm	1900
	最大行驶速度 Maximum traveling speed	km/h	13
	斗容 Bucket capacity	m ³	0.4
发动机 Engine			
	品牌 Brand	KUBOTA	
	型号 Model	V2403-CR-TE5B	
	类型 Type	4缸、水冷、柴油发动机 4-cylinder, water cooling, diesel engine	
	排放标准 Emission standard	EPA Tier4F / EU Stage5	
	功率 Power	kW/rpm	48.6/2700
	最大扭矩 Maximum torque	N·m/rpm	198.5/1900
电器系统 Electrical System			
	起动机马达 Starting motor	V/kW	12/2.0
	发电机 Generator	V/A	12/60
	蓄电池 Battery	Ah	120
加油量 Fueling Amount			
	液压油箱 Hydraulic oil tank	L	35
	燃油箱 Fuel tank	L	75
液压系统 Hydraulic System			
	标准流量 Standard discharge	L/min	67
	大流量 Large discharge	L/min	98
	标准工作压力 Standard working pressure	bar	210
	大流量工作压力 Large-discharge working pressure	bar	165

