

VT8

The top among the manual lighting towers with integrated generator, multifunction control panel and 3 kVA outlet socket. Available with Perkins or Kubota engine.

- Vertical mast
- 8m max height
- Galvanized telescopic sections
- 5 adjustable stabilizers
- Certified wind stability up to 110 Km/h
- Manual lifting system
- Rising system with manual winch
- 4 x 1000W metal halide floodlights
- On/Off switches one for each lamp
- Low speed towing trailer, single axle
- 3 kVA 230V outlet socket
- 8 kVA 230V power generator (50/60 Hz)
- Coiled cable to supply the lamps
- Pockets and central hook for lifting the complete structure with crane or forklift
- 340° mast rotation
- 75 l fuel metal tank
- Lockable doors
- Series of alarms to prevent engine failures
- Running time of more than 40 hours
- Hour counter
- Emergency stop button

TECHNICAL DATA

Dimensions and weight

Min Dim. (cm) 265x130x246

Max Dim. (cm) 265x246x800

Weight (Kg) 719

Illuminated area

4000 m²

Engines available

Perkins 403-C11, diesel, water cooled, 3 cylinders, 1500/1800 rpm

Kubota D1105, diesel, water cooled, 3 cylinders, 1500/1800 rpm

Quantity per container

20 feet: 7 units

40 feet: 14 units



VT8 4x1000W MH

VT8 LIGHT TOWER - INDONESIA



1 Linktower 4x400W MH can be connected to the extra outlet of a VT8 (3KVA)



ILLUMINATED AREA: 4.000 m²

