



Innovative system for the rental industry.

The outstanding features of PACLITE four-cycle rammers are the compact design and strong performance. The long shoe stroke, high percussion rate and high stroke energy combined with fast advance travel achieve excellent results in trenches and channels.



Features and Benefits

- Engine Protection system (eps).
- Two-stage air filtration (Robin ER12) system with cyclone prefilter: high filter capacity thanks to premium quality. Easy access to servicing points.
- Automatic oil level.
- Low vibrating handle.
- Protective cover with 'tachymeter',
- Measuring the speed and duration of work.
- Strong lifting eye
- Pull wheels mounted on frame for easy loading.
- Engine shut off integrated in the throttle
- Narrow frame 380mm.
- Bellow of German make.



Code	CRX68R	CRX68H
Model	CRX68 Robin Subaru	CRX68 Honda
Operating mass (kg)	71	71
Dimensions L x W x H (mm)	737x360x1025	737x360x1025
Engine	Robin ER12	Honda GX100
Power max output. hp (Kw)	2,6 (3,5)	2,2 (3)
Fuel Capacity (l)	4	4
Foot dimension l x L (mm)	285x334	285x334
Stroke (mm)	70	70
Impact Force Max. (kN)	16	16
Impact Number / Min	650-700	650-700
Compaction depth (cm)	45	45
Speed (m/min)	10-13	10-13
Compacted area (m ² /h)	260	260
Vibrations* m/sec ² /utilisation (hrs)	6,4	6,4
Dual air cleaner	yes	no
Sound pressure level (dB)	91	91

* Minimum vibration levels measured to EN500-4

