

REVERSIBLE VIBRATORY PLATES VDR



Application:

Powerful compaction machines, especially suitable for soil compaction. Alternatively can be used also for compaction of asphalt layers or pavement (particularly for reversible plates up to 250 kg).



| | | VDR 22 | VDR 26 | VDR 32 | VDR 52 | VDR 63 |
|------------------------------|--------|-----------|-----------|-----------|-----------|-----------|
| Weight | kg | 120 | 160 | 210 | 330 | 430 |
| Compact. plate dimens. (WxL) | mm | 400 x 630 | 450 x 700 | 500 x 750 | 600 x 895 | 750 x 900 |
| Frequency | Hz | 100 | 95 | 90 | 75 | 70 |
| Centrifugal force | kN | 22 | 26 | 32 | 52 | 63 |
| Max. speed | m/min | 24 | 22 | 22 | 22 | 20 |
| Engine | | HONDA | HONDA | HONDA | HONDA | HONDA |
| Type | | GX 160 | GX 200 | GX 200 | GX 270 | GX 390 |
| Fuel | | petrol | petrol | petrol | petrol | petrol |
| Net power/RPM | kW/RPM | 3,6/3600 | 4,1/3600 | 4,1/3600 | 6,3/3600 | 8,7/3600 |